



ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwäehnt.

• Chiave inclusa

• Key included

• Schlüssel inbegriffen

| Cod. MT | Mandrino Spindle Spindel | I (n1:n2) | RPM max n2 | Coppia Max Max Torque Max Drehmoment M2 (Nm) | Reversibile 180° 180° Reversible 180° umsetzbar | Lubrificazione int. Coolant through Innenkuehlung Pmax (bar) | Lubr.esterna Ext. coolant Aussenkuehlung | Lav. secco Dry-run Trocken Bearb. | A | A1 | B | CHIAVI NON INCLUSE Keys not included Schlüssel nicht einbegriffen | |
|------------|--------------------------|-----------|------------|--|---|--|--|-----------------------------------|--------|----|----|---|------------------|
| | | | | | | | | | | | | | |
| NKM0610125 | ER A 25 | 1:1 | 6000 | 70 | X | - | X | X | 89.53 | - | 68 | CHUB46 | CHUB27 |
| NKM0610132 | ER A 32 | 1:1 | 6000 | 70 | X | - | X | X | 91.53 | - | 68 | CHUB46 | CHUB32 |
| NKM0610140 | ER40 | 1:1 | 6000 | 70 | X | - | X | X | 108.16 | - | 68 | CHUB46 | CHSTER40 |
| NKM0610225 | ER A 25 | 1:1 | 6000 | 70 | X | 100 (diag. 2) | X | X | 89.53 | - | 79 | CHUB46 | CHUB27 |
| NKM0610232 | ER A 32 | 1:1 | 6000 | 70 | X | 100 (diag. 2) | X | X | 91.53 | - | 79 | CHUB46 | CHUB32 |
| NKM0610240 | ER40 | 1:1 | 6000 | 70 | X | 100 (diag. 2) | X | X | 108.16 | - | 79 | CHUB46 | CHSTER40 |
| NKM0612219 | Ø22x19 | 1:1 | 6000 | 70 | X | - | X | X | - | 80 | 68 | CHUB46 | CH_VTCROCE_M10 * |

CHIAH CHYUN

MOD: CT1/CT2/CT3-52/65/76 YM/Y2M/Y2MS

MODULO MOTORIZZATO ASSIALE H=65mm

Axial driven tool H=65mm

Axial angetriebenes Werkzeug H=65mm

Subject to change without notice.

M.T. srl

Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341
47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@mtmarchetti.com
http://www.mtmarchetti.com



CCM150-1-20