



ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwäehnt.

• Chiave inclusa

• Key included

• Schlüssel inbegriffen

Cod. MT	Mandrino Spindle Spindel	I (n1:n2)	RPM max n2	Coppia Max Max Torque Max Drehmoment M2 (Nm)	Lubrificazione int. Coolant through Innenkuehlung Pmax (bar)	Lubrificazione est. Ext. coolant Aussenkuehlung	Lav. secco Dry-run Trocken Bearb.	A	B	CHIAVI NON INCLUSE Keys not included Schlüssel nicht einbegriffen	
MSL0570132	ER32	1:1	6000	105	-	X	X	91.41	55	MNZ0410005 ▪	CHSTER32
MSL0570232	ER32	1:1	6000	105	100 (diag. 2)	X	X	91.41	67.5	MNZ0410005 ▪	CHSTER32
MSL0570125	ER25	1:1	6000	105	-	X	X	88.41	55	MNZ0410005 ▪	CHSTER25
MSL0570225	ER25	1:1	6000	105	100 (diag. 2)	X	X	88.41	67.5	MNZ0410005 ▪	CHSTER25

CMZ

MOD:TL25AM/AMS/BM/BMS - TL20M/MS/TM - TA15-20-25-30M/Y/MS/MY/YS 12ST. - TC15-20-25-30-35M/Y/MS/MY/YS 12ST./16ST.
TD15-20-25-30-35-45-55M/Y/MS/MY/YS 12ST./16ST.

MODULO MOTORIZZATO ASSIALE PER CONTROMANDRINO H=55mm

Axial driven tool for subspindle H=55mm

Axial angetriebenes Werkzeug fuer Gegenspindel H=55mm

Subject to change without notice.

M.T. srl

Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341
47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@mtmarchetti.com
http://www.mtmarchetti.com



CMZ155-2-10