



| Cod. MT | Mandrino Spindle Spindel | I (n1:n2) | RPM max n2 | Coppia Max Max Torque Max Drehmoment M2 (Nm) | Lubrificazione est. Ext. coolant Aussenkuehlung | Lav. secco Dry-run Trocken Bearb. | A | A1 | D | L | CHIAVI INCLUSE Keys included Schlüssel inbegriffen | |
|------------|--------------------------------|--------------|------------------|---|---|---|-------|----|------|------|--|----------------|
| MSL0230120 | ER20 | 1:1 | 6000 | 40 | X | X | 85.16 | - | - | - | CHUB36 | CHSTER20 |
| MSL0230125 | ER25 | 1:1 | 6000 | 40 | X | X | 86.16 | - | - | - | CHUB36 | CHSTER25 |
| MSL0230516 | Ø16x17 | 1:1 | 6000 | 40 | X | X | - | 65 | 16 | 17 | CHUB36 | CH_VTCROCE_M08 |
| MSL0230522 | Ø22x19 | 1:1 | 6000 | 40 | X | X | - | 66 | 22 | 19 | CHUB36 | CH_VTCROCE_M10 |
| MSL0230519 | Ø3/4"x3/4" | 1:1 | 6000 | 40 | X | X | - | 65 | 3/4" | 3/4" | CHUB36 | CH_VTCROCE_M08 |

CMZ

MOD:TL25AM/AMS/BM/BMS - TL20M/MS/TM - TA15-20-25-30M/Y/MS/MY/YS 12ST. - TC15-20-25-30-35M/Y/MS/MY/YS 12ST./16ST.
TD15-20-25-30-35-45-55M/Y/MS/MY/YS 12ST./16ST.

MODULO MOTORIZZATO ORIENTABILE ±90°

±90° adjustable angle driven tool

Angetriebenes Werkzeug schwenkbar ±90°

Subject to change without notice.

M.T. srl

Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341

47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@tmarchetti.com
http://www.tmmarchetti.com



CMZ333-2-00

09/2025