



Cod. MT	Mandrino Spindle Spindel	I (n1:n2)	RPM max n2	Coppia Max Max Torque Max Drehmoment M2 (Nm)	Reversibile 180° 180° Reversible 180° umsetzbar	Lubrificazione int. Coolant through Innenkuehlung Pmax (bar)	Lubr. esterna Ext. coolant Aussenkuehlung	Lav. secco Dry-run Trocken Bearb.	A	A1	B	CHIAVI NON INCLUSE Keys not included Schlüssel nicht einbegriffen	
DW03200340	ER40	1:1	3000	210	X	-	X	X	140.2	-	75	NZL0010023	CHSTER40
DW03200440	ER40	1:1	3000	210	X	100 (diag. 2)	X	X	140.2	-	86	NZL0010023	CHSTER40
DW03200350	ER50	1:1	3000	210	X	-	X	X	153.5	-	75	NZL0010023	CHSTER50
DW03200450	ER50	1:1	3000	210	X	100 (diag. 2)	X	X	153.5	-	86	NZL0010023	CHSTER50
DW03200150	ERA50	1:1	3000	210	X	-	X	X	145.3	-	75	NZL0010023	CHUB50
DW03200250	ERA50	1:1	3000	210	X	100 (diag. 2)	X	X	145.3	-	86	NZL0010023	CHUB50
DW01390240	Weldon 40	1:1	3000	210	X	-	X	X	-	175.5	75	-	-
DW01390140	Weldon 40	1:1	3000	210	X	100 (diag. 2)	X	X	-	175.5	86	-	-

- Chiave inclusa
- Key included
- Schlüssel inbegriffen

DN SOLUTIONS (DOOSAN) BMT 85

MOD: PUMA 600M/LM/LY - PUMA 700M/LM/LY - PUMA 800M/LM/LY
 PUMA 600M/LM/LY(II) - PUMA 700M/LM/LY(II) - PUMA 800M/LM/LY(II) - VT900M/TM - V9300M

MODULO MOTORIZZATO ASSIALE H=85mm

Axial driven tool H=85mm

Axial angetriebenes Werkzeug H=85mm

Subject to change without notice.

M.T. srl

Via Casino Albini 480
 Tel. 0541/956034-957884
 Fax 0541/956341
 47842 S. GIOVANNI IN M. (RN)
 e-mail: mtma@mtmarchetti.com
 http://www.mtmarchetti.com



DW 0150-5-10