



| Cod. MT | Mandrino Spindle Spindel | I (n1:n2) | RPM max n2 | Coppia Max Max Torque Max Drehmoment M2 (Nm) | Reversibile 180° 180° Reversible 180° umsetzbar | Lubrificazione int. Coolant through Innenkuehlung Pmax [bar] | Lubrificazione est. Ext. coolant Aussenkuehlung | Lav. secco Dry-run Trocken Bearb. | CHIAVI NON INCLUSE Keys not included Schlüssel nicht einbegriffen | | | |
|-------------|--------------------------------|--------------|------------------|---|---|---|---|---|---|------------|------------|---|
| DW 01890316 | ERA16 | 1:1 | 6000 | 25 | X | - | X | X | CHUB30 | CHUB19_SP3 | CHTAER16ZC | ▪ |
| DW 01890416 | ERA16 | 1:1 | 6000 | 25 | X | 70 | X | - | CHUB30 | CHUB19_SP3 | CHTAER16ZC | ▪ |

| |
|-------------------------|
| • Chiave inclusa |
| • Key included |
| • Schlüssel inbegriffen |

HARD INGE

MOD: T-42 16ST. - TALENT 42/51 12/16ST. - TALENT TT42/51 16ST. - CONQUEST H51 16ST. (BMT45)

MODULO MOTORIZZATO RADIALE DISASSATO IN Z 36mm

Radial driven tool re-directed in Z by 36mm

Radial angetriebenes Werkzeug achsversetzt in Z um 36mm

Subject to change without notice.

M.T. srl

Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341

47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@mtmarchetti.com
http://www.mtmarchetti.com



HRD030-1-10