



ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwäehnt.

- Chiave inclusa
- Key included
- Schlüssell einbegriffen

Cod. MT	Mandrino Spindle Spindel	I (n1:n2)	RPM max n2	Coppia Max Max Torque Max Drehmoment M2 (Nm)	N°Utensili N°Tools N°Werkzeuge	Reversibile 180° 180° Reversible 180° umsetzbar	Lubr.esterna Ext. coolant Auslenkuehlung	Lav. secco Dry-run Trocken Bearb.	A	B	CHIAVI NON INCLUSE Keys not included Schlüssell nicht einbegriffen		
MNL1060225	ER25	1:1	10000	40	2	X	X	X	137.96	68	CHUB36	CHSTER25	-
MNL1060325	ERA25	1:1	10000	40	2	X	X	X	126.5	68	CHUB38	CHUB27	CHTAER25ZC •
MNL1240225	ER25+ER25	1:1	10000	40	2+2	X	X	X	137.96	137.96	CHUB36	CHSTER25	-
MNL1240325	ERA25+ERA25	1:1	10000	40	2+2	X	X	X	126.5	126.5	CHUB38	CHUB27	CHTAER25ZC •

DMG-MORI
 NL1500/2000/2500/3000 12 ST. - NLX1500/2000/2500/3000 12 ST. - NLX2500 2ND GEN. 10/12ST. - NLX4000 - NZL2000/2500 - NZX2500 (BMT60)
 NT4200/4250/4300/5400 - NTX2000/2500/3000 2ND GEN. 10ST. - CTX2500 (BMT60)
MODULO MOTORIZZATO ASSIALE 2 USCITE IN Y 10000 RPM
 Axial Single side twin head driven tool in Y 10000 rpm
 Axial angetriebenes Werkzeug 2 Ausgaenge in Y 10000 rpm

M.T. srl
 Via Casino Albini 480
 Tel. 0541/956034-957884
 Fax 0541/956341
 47842 S. GIOVANNI IN M. (RN)
 e-mail: mtma@mtmarchetti.com
 http://www.mtmarchetti.com



MNL260-1-11

Subject to change without notice.