



ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwäehnt.

- Chiave inclusa
- Key included
- Schluessel inbegriffen

Cod. MT	Mandrino Spindle Spindel	I (n1:n2)	RPM max n2	Coppia Max Max Torque Max Drehmoment M2 (Nm)	Reversibile 180° 180° Reversible 180° umsetzbar	Lubrificazione int. Coolant through Innenkuehlung Pmax (bar)	Lubrificazione est. Ext. coolant Aussenkuehlung	Lav. secco Dry-run Trocken Bearb.	A	H	CHIAVI NON INCLUDE Keys not included Schluessel nicht inbegriffen		
NKM2490216	ER16	1:1	12000	30	X	-	X	X	115.15	82	CHUB17	CHMNER16	
NKM2490520	ERA20	1:1	12000	30	X	100 (diag. 2)	X	X	116.15	87	MNLO210007	CHUB22	CHTAER20ZC *
NKM2490225	ER25	1:1	12000	30	X	-	X	X	115.61	82	MNLO210007	CHSTER25	
NKM2490425	ER25	1:1	12000	30	X	100 (diag. 2)	X	X	128.11	87	MNLO210007	CHSTER25	

NAKAMURA-TOME

WT150/250 - WT15011/25011 - WTW150 - WTS150 - SUPER NTM3 - SUPER NTJ - SC150/200/250 - SC20011 12/16 ST.
SC30011 16ST. - NTY3 150(V)/250 - TW10M/MY/MM/MMY/MMYY-TW20M/MY/MM/MMY/MMYY 16ST. - WY 150(V)/250 - AS200 15/12 ST. - AS200L 15/12 ST.

MODULO MOTORIZZATO ASSIALE 2 USCITE IN Y 12000 RPM H=55mm
Axial single side twin head driven tool in Y 12000 rpm H=55mm
Axial angetriebenes Werkzeug 2 Ausgaenge in Y 12000 rpm H=55mm

M.T. srl

Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341
47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@mtmarchetti.com
http://www.mtmarchetti.com



NKM260-2-11

Subject to change without notice.

03/2026