



ATTENZIONE - ATTENTION - ACHTUNG

- Per lo smontaggio degli utensili utilizzare sempre la chiave di contrasto come indicato nel manuale d'uso.
- For disassembly of the tools use always the contrast key as mentioned in the user instructions.
- Fuer das Abmontieren der Werkzeuge immer den Gegenschlüssel benutzen wie in der Bedienungsanleitung erwäehnt.

- Chiave inclusa
- Key included
- Schlüssel inbegriffen

CHIAVI NON INCLUSE
Keys not included
Schlüssel nicht einbegriffen

| Cod. MT | Mandrino Spindle Spindel | I (n1:n2) | RPM max n2 | Coppia Max Max Torque Max Drehmoment M2 (Nm) | Reversibile 180° 180° Reversible 180° umsetzbar | Lubr.esterna Ext. coolant Aussenkuehlung | Lav. secco Dry-run Trocken Bearb. | A | B | | | | | |
|-------------|--------------------------|-----------|------------|--|---|--|-----------------------------------|-------|-------|----------|----------|--------------|--------------|--------------|
| DW 00720132 | ER32+ER25 | 1:1 | 6000 | 100 | X | X | X | 93.66 | 80.16 | CHSTER32 | CHSTER25 | OKU0650004 • | - | - |
| DW 00722520 | ERA25+ERA20 | 1:1 | 6000 | 100 | X | X | X | 65 | 55.5 | CHUB22 | CHUB27 | OKU0650004 • | CHTAER20ZC • | CHTAER25ZC • |

ROMI

MOD: GL 350M/Y/S

MODULO MOTORIZZATO ASSIALE BISPORGENTE H=72mm

Axial opposite face driven tool H=72mm

Axial angetriebenes Werkzeug halb vorspringend H=72mm

Subject to change without notice.

M.T. srl

Via Casino Albini 480
Tel. 0541/956034-957884
Fax 0541/956341
47842 S. GIOVANNI IN M. (RN)
e-mail: mtma@mtmarchetti.com
http://www.mtmarchetti.com



ROM240-3-10