



Cod. MT	Mandrino Spindle Spindel	I (n1:n2)	RPM max n2	Coppia Max Max Torque Max Drehmoment M2 (Nm)	Reversibile 180° 180° Reversible 180° umsetzbar	Lubrificazione int. Coolant through Innenkuehlung	Lubrificazione est. Ext. coolant Aussenkuehlung	Lav. secco Dry-run Trocken Bearb.	CHIAVI NON INCLUSE Keys not included Schlüssel nicht einbegriffen		
						Pmax (bar)					
DW 01891316	ERA16	1:2	12000	15	X	-	X	X	CHUB30	CHUB19_SP3	CHTAER16ZC
DW 01891416	ERA16	1:2	12000	15	X	70	X	-	CHUB30	CHUB19_SP3	CHTAER16ZC

- Chiave inclusa
- Key included
- Schlüssel inbegriffen

SMEC (SAMSUNG)

MOD: PL1600M/CM - PL2000M - SL15M - NS 2100SY

MODULO MOTORIZZATO RADIALE MOLTIPLICATO I=1:2 DISASSATO IN Z 36mm

Radial geared-up I=1:2 driven tool re-directed in Z by 36mm

Radial angetriebenes Werkzeug uebersetzt I=1:2 achsversetzt in Z um 36mm

Subject to change without notice.

**M.T. srl**

Via Casino Albini 480  
Tel. 0541/956034-957884  
Fax 0541/956341  
47842 S. GIOVANNI IN M. (RN)  
e-mail: mtma@mtmarchetti.com  
http://www.mtmarchetti.com



SMG030-4-30