



Cod. MT	Mandrino Spindel Spindel	I (n1:n2)	RPM max n2	Coppia Max Max Torque Max Drehmoment M2 (Nm)	Reversibile 180° 180° Reversible 180° umsetzbar	Lubrificazione int. Coolant through Innenkuehlung Pmax (bar)	Lubr. esterna Ext. coolant Aussenkuehlung	Lav. secco Dry-run Trocken Bearb.	A	A1	B	CHIAVI NON INCLUSE Keys not included Schlüssel nicht einbegriffen	
DW 03190340	ER40	1:1	3000	210	X	-	X	X	140.2	-	75	NZL0010023	CHSTER40
DW 03190440	ER40	1:1	3000	210	X	100 (diag. 2)	X	X	140.2	-	86	NZL0010023	CHSTER40
DW 03190350	ER50	1:1	3000	210	X	-	X	X	153.5	-	75	NZL0010023	CHSTER50
DW 03190450	ER50	1:1	3000	210	X	100 (diag. 2)	X	X	153.5	-	86	NZL0010023	CHSTER50
DW 03190150	ERA50	1:1	3000	210	X	-	X	X	145.3	-	75	NZL0010023	CHUB50
DW 03190250	ERA50	1:1	3000	210	X	100 (diag. 2)	X	X	145.3	-	86	NZL0010023	CHUB50
DW 01290240	Weldon 40	1:1	3000	210	X	-	X	X	-	175.5	75	-	-
DW 01290140	Weldon 40	1:1	3000	210	X	100 (diag. 2)	X	X	-	175.5	86	-	-

- Chiave inclusa
- Key included
- Schlüssel inbegriffen

SMEC (SAMSUNG)

MOD: SL60/65 MC - PL60/65/70/80 MC - SLV1000M - SL6500/8500M

MODULO MOTORIZZATO ASSIALE H=110mm

Axial driven tool H=110mm

Axial angetriebenes Werkzeug H=110mm

Subject to change without notice.

**M.T. srl**

Via Casino Albini 480

Tel. 0541/956034-957884

Fax 0541/956341

47842 S. GIOVANNI IN M. (RN)

e-mail: mtma@mtmarchetti.com

http://www.mtmarchetti.com



SMG150-3-20